

UT60D



UT60D

SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	340mV/3.4V/34V/340V/∞00V	±(0.8%+∞)
AC Voltage	3.4V/34V/340V/750V	±(∞.5%+3)
Band Width	∞00kHz - 3db	✓
DC Current	340μA/3400μA/34mA/340mA/∞0A	±(∞.2%+2)
AC Current	340μA/3400μA/34mA/340mA/∞0A	±(∞%+3)
Resistance	340Ω/3.4kΩ/34kΩ/340kΩ/3.4MΩ/34MΩ	±(∞%+2)
Frequency	3.4kHz/34kHz/340kHz/3.4MHz/34MHz	±(0.2%+2)
RPM	34k/340k/3.4M/34M/340M	±(0.2%+2)
Special Functions		
Fused ∞0A Range	✓	
Auto Ranging	✓	
Diode	✓	
Continuity Buzzer	✓	
Data Hold	✓	
RS232C	✓	
Display Backlight	✓	
Full Icon Display	✓	
Sleep Mode	✓	
Low Battery Display	✓	
Input Impedance for DC Voltage Measurement	Around ∞0MΩ	
Max. Display	3400	

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	63 x 31 mm
Product Colour	Red and Grey
Product Net Weight	320g
Product Size	177 x 85 x 40 mm
Standard Accessories	Test Lead, Battery, English Manual, Test Clip, RS232C Interface Cable, Software
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	40 pcs
Standard Carton Measurement	598 x 418 x 340 mm (0.085 CBM Per Standard Carton)
Standard Carton Gross Weight	26kg