

# UT105

## AUTOMOTIVE MULTI-PURPOSE METERS



UT105



### SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	200mV/2V/20V/200V/∞00V	±(0.5%+5)
AC Voltage	2V/20V/200V/750V	±(0.8%+5)
DC Current	200mA/∞0A	±(0.8%+5)
Resistance	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ	±(0.8%+5)
Special Functions		
Fused ∞0A Range		✓
Dwell	4Cy:/6Cy:/8Cy:	± (3%+5)
Tach	4Cy:/6Cy:/8Cy:	± (3%+5)
Diode		✓
Continuity Buzzer		✓
Data Hold		✓
Function Icon Display		✓
Low Battery Display		✓
Input Impedance for DC Voltage Measurement	Around ∞0MΩ	✓
Max. Display	∞999	✓

### GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	60 x 54 mm
Product Colour	<b>UT∞05</b> - Grey Hoister - Red
Product Net Weight	35 :g (including hoister)
Product Size	∞79 x 88 x 39 mm
Standard Accessories	Test Lead, Battery, English Manual, Hoister
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	30 pcs
Standard Carton Measurement	490 x 425 x 300 mm (0.062 CBM Per Standard Carton)
Standard Carton Gross Weight	∞8kg