

WECL:59-03-0151



EN:61010-1  
EN:61326-1  
EN:61243-3



■ UT15A

**SPECIFICATIONS**

Specifications	Range	Best Accuracy		
		UT15A	UT15B	UT15C
Model	12V	0~12V	0~12V	0~12V
	24V	19V±2V	19V±2V	19V±2V
	50V	48V±6V	48V±6V	48V±6V
LED AC/DC Voltage Indication (V)	120V	110V±20V	110V±20V	110V±20V
	230V	200V±20V	200V±20V	200V±20V
	400V	340V±30V	340V±30V	340V±30V
	690V	520V±30V	520V±30V	520V±30V
	Phase Rotation Test	Operating Voltage: 0V~690V Frequency: 50Hz~60Hz	✓	✓
Single Lead(L2)Voltage Detection	Operating Voltage: 0V~690V Frequency: 50Hz~400Hz	✓	✓	✓
Continuity Test	Resistance: 0~100KΩ Beeper and LED Light Indicator		✓	✓
Polarity Detection	Positive & Negative	✓	✓	✓
<b>Features</b>				
Water-Proof (IP65)		✓	✓	✓
Auto Range		✓	✓	✓
Work Light		✓	✓	✓
Low Battery Indication	Short circuit two leads,LED and beeper off when the battery is low	✓	✓	✓
LCD AC/DC Voltage Display	24V~690V			±(3%+5)



UT15B ■

WECL:59-03-0152



**GENERAL CHARACTERISTICS**

Power	1.5V Batteries (R03) × 2
LCD Size	UT15C-23mm × 12mm
Product Color	Red and Grey
Product Net Weight	210g
Product Size	275mm × 51mm × 30mm
Standard Accessories	Batteries
Standard Individual Packing	Blister, English Manual
Standard Quantity Per Carton	30PCs
Standard Carton Measurement	440mm × 295mm × 455mm (0.079 CBM Per Standard Carton)
Standard Carton Gross Weight	17Kg

■ UT15C

WECL:59-03-0153

