



UT511



UT513

**SPECIFICATIONS**

Basic Functions	Range	Best Accuracy	
		UT511	UT513
Insulation Resistance	500kΩ ~ 10GΩ 1MΩ~1000GΩ	±(2%+15)	±(5%+5)
Low Resistance	1000Ω	±(1%+3)	
Testing Voltage	100V/250V/500V/1000V 1000V/1500V/2500V/5000V	0~20%	0~20%
DC Voltage	1000V	±(1%+3)	±(1%+3)
AC Voltage	750V	±(1.5%+3)	±(1.5%+3)
Special Functions			
Auto Ranging		✓	✓
Short Circuit Current		<2mA	<1.3mA
Data Logging		18	18
Data Recall		✓	✓
Sleep Mode		✓	✓
Polarization index (PI)		✓	✓
Dielectric Absorption(DAR)		✓	✓
Timer	Within 30 minutes	✓	✓
Compare		✓	✓
Battery Display		✓	✓
Display Backlight		✓	✓
Over Range and High Voltage Warning		✓	✓
USB			✓
Max. Display	9999	✓	✓
Analogue Bar Graph		✓	✓

**GENERAL CHARACTERISTICS**

Power	<b>UT511</b> - 1.5V Battery (R14) x 8 <b>UT513</b> - 1.5V Alkaline Battery (LR14) x 8
LCD Size	123 mm x 58 mm
Product Color	Grey
Product Net Weight	2kg
Product Size	202 x 155 x 94 mm
Standard Accessories	<b>UT511</b> - A pair of one plug test lead to one alligator clip, A pair of two plugs test lead to one alligator clip, Batteries, English Manual, Tool Box. <b>UT513</b> - A pair of one plug test lead to one alligator clip, A pair of two plugs test lead to one alligator clip, Batteries, English Manual, Tool Box, USB Interface Cable, Software
Optional Accessories*	Power Adapter
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	5 pcs
Standard Carton Measurement	600 x 350 x 320 mm (0.067 CBM Per Standard Carton)
Standard Carton Gross Weight	Around 13kg

\* Available at Extra Cost