



Fluke i200S AC Current Clamp

Small sized AC current clamp

Fluke Current clamps are the ideal tools to extend the current ranges of Fluke tools. The i200s is a dual range 20A and 200A ac current clamp with voltage output via a safety insulated BNC connector. A dual banana to BNC adapter is supplied to allow the i200s to be connected to multimeters with banana inputs.

- Companion to your scopemeter, power quality meter or digital multimeter to measure up to 200 A AC
- Included adapter for DMM's
- Two ranges: 20 A & 200A, 10 or 100 mV/ Amp output
- Take accurate current readings without breaking the circuit
- Max. conductor Ø 20 mm
- CAT III 600V safety rating

Specifications	
Nominal current range	20 A 200 A
Continuous current range	0.1 A - 24 A 0.5 A - 200 A
Maximum Non-Destructive Current	240 A
Lowest measurable current	0.1 A
Basic Accuracy	1.5% +0.5 A (48-65 Hz) (% reading + floorspec)
Useable frequency	40 Hz - 10 kHz
Output level(s)	100 mV/A 10 mV/A

Safety Specifications	
Safety	CAT III, 600 V
Maximum voltage	600 V AC

Mechanical & General Specifications	
Warranty	1 year
Maximum conductor diameter	20 mm
Maximum conductor size (busbar)	20 x 5 mm
Output cable length	2.0 m
BNC Adapter	Yes
BNC to banana adapter included	Yes

華輝無線電行有限公司
Welfare Electronic Component Ltd.

寫字樓 Main office:
香港九龍深水埗長沙灣道199號長樂大廈1樓全層
1/F, Cheong Lok Building, 199 Cheung Sha Wan Road,
Sham Shui Po, Kowloon, Hong Kong

☎ 客戶服務熱線
(852) **3182 0888**

門市 Retail Shop:
香港九龍深水埗鴨寮街201號明珠樓地下及1樓全層
G/F & 1/F, Ming Chu Building, 201 Apliu Street,
Sham Shui Po, Kowloon, Hong Kong

Fax: (852) 3182 0808
E-mail: cs@wecl.com.hk
WECL.com.hk

