

Material moisture,
air humidity
and temperature



- Precise measurement of wood moisture thanks to stored characteristics curves for e.g. beech, spruce, larch, oak, pine, maple
- Air temperature and humidity for monitoring drying processes
- Characteristics curves for cement screed, concrete, plaster, anhydrite screed, cement mortar, lime mortar, brick
- Hold function for easy measurement value readout
- Auto-test function

Testo 606-1/-2

Technical data

Material moisture

Measuring range: 0 to 90%

Resolution: 0.1

Accuracy: $\pm 1\%$ (conductivity)

Air humidity (606-2 only):

Measuring range: 0 to 100%RH

Resolution: 0.1%RH

Accuracy: $\pm 2.5\%$ RH (5 to 95%rF)

Units: %RH, wet bulb, dewpoint

Air temperature (606-2 only)

Measuring range: -10 to 50°C

Resolution: 0.1°C

Accuracy: $\pm 0.5\text{ }^{\circ}\text{C}$

Units: $^{\circ}\text{C}/^{\circ}\text{F}$

Oper. temp.: -10 to 50 $^{\circ}\text{C}$

Battery type: Alkaline (2 x AAA)

Battery life: 606-1: 200 h.

606-2: 130 h.

(average, without display illumination)

Dimensions

(incl. protective cap): 119 x 46 x 25 mm

Included in delivery:

Calibration protocol · Wrist strap

Belt holder · Protective cap · Batteries

606-1 Product code: 59-19-6060

606-2 Product code: 59-19-6062