3M[™] Temperature Loggers

TL30 and TL30V

Monitor temperature sensitive products to help verify product safety and shelf life

- Easy to use software
- Cost-effective reusability
- One unit for short or long term monitoring

When you or your customers want to know temperature conditions during shipment, all the data you need now comes in a small, feature-loaded package:

- Cost effective alternative to single use monitors
- Reliable and accurate recording of up to 50,000 data points of time and temperature
- High performance battery for up to 12 months use with short circuit protection and low battery indicator
- LED flashing options to visually monitor the temperature exceeding programmed limits
- EN 12830 compliant for the transport and storage of chilled or frozen foods



System Components

- 3M[™] Temperature Logger TL Series PC Software
- Uses any standard mini USB cable
- Food grade plastic bag to be used when the logger is placed in contact with food





Monitor package temperature for confidence in freshness and shelf life during shipment and storage.



Flexibility and ease of use for your temperature monitoring needs

Primary Applications

3M[®]Temperature Logger TL30 is recommended for recording temperatures during transportation and/or storage of these temperature-sensitive products:

- Fresh produce, fruit, and vegetables
- Frozen food items
- Seafood
- Meat and poultry
- Milk-based products
- Chemical products

3M[®]Temperature Logger TL30V includes a certificate of accuracy for factory calibration and is recommended for recording temperatures during transportation and/or storage of these temperature-sensitive products:

- Pharmaceuticals
- · Medical and biological products, and clinical samples
- Chemical products requiring regulatory documentation
- Other perishable products requiring validation documentation

Confidence in the data with TL30V

Each TL30V undergoes verification testing. A verification certificate can be downloaded from the product web page.

- Three-point temperature verification at -10 C, 10 C and 50 C.
- Verification in ISO 17025 laboratory accredited by A2LA, NIST Traceable
- Easy one-click reporting in read-only Excel format





Track and Trace Solutions 3M Center, Building 225-4N-4 St. Paul, MN 55144-1000

St. Paul, MN 55144-1000 1-800-944-3512 www.3m.com/temperaturelogger Please recycle. Printed in U.S.A. © 3M 2010. All rights reserved. 3M is a trademark of 3M

Typical Performance Properties

Temperature Range	-40°C (-40°F) to 80°C (176°F)
Temperature Accuracy	+/- 0.5°C (+/-0.9°F)
Temperature Resolution	0.1°C (0.3°F)
Memory Data Points	50,000
Data Logging Frequency	1 to 120 minutes
Auto Start-Up Delay	0 to 168 hours (0 to 7 days)
Manual Start-Up Delay	0 to 240 minutes (0 to 4 hours)
Range of Monitoring Time	1 to 360 days
Water Splash Resistance	NEMA 3R
Size	70 mm x 44 mm x 11 mm (2.8 in x 1.7 in x 0.4 in)
Weight	28 grams (0.99 oz.)



•C	Set(3)	Help(H)						
	s 🗞 🗛 🔃						V1 ID:AM	801033
tup	Data Table Graph	Summary R	eport					
	Print	All Data		Data Exceed Limit Data of Graphic zoom				
	UTC(+00:00)	Origin(+10:00)	Destination(-06:00)	*	4	Alamiti	Abrelow	ă
54	2010-08-18 15:40	2010-08-19 01:40	2010-08-18-09140	22.4	72.3	•		
55	2010-08-18 15-55	2010-08-19 01:55	2010-08-18-09:55	22.2	72.0			
56	2010-08-18 15:10	2010-08-19 02:10	2010-08-18 10:10	22.0	71.6			
57	2010-08-18 18:25	2010-08-19 02:25	2010-08-18 10:25	21.6	71.2			
58	2010-08-18 16:40	2010-08-19 02:40	2010-08-18 10:40	21.8	71.2			
59	2010-08-08 18:55	2010-08-19 02:55	2010-08-18 10:55	21.7				
60	2010-08-08 17:10	2010-08-19 03:10	2010-08-18 11:10	21.6	70.9			
61	2010-08-08 17:25	2030-08-29-03-25	2010-08-18 11:25	21.5	20.7			
62	2010-08-08 17:40	2030-08-29-03+40	2010-08-18 11/40	21.4	20.5			
63	2010-08-08 17:55	2010-08-19 03:55	2010-08-18 11:55	21.3	70.3			
64	2010-08-18:10	2010-08-19 04:10	2010-08-18 12:10	21.1	70.0			
65	2010-00-10 10:25	2010-08-19 04:25	2010-08-18 12:25	21.0	69.0			
66	2010-08-18:40	2010-08-19 04:40	2010-08-18 12:40	20.8	69.4			
67	2010-08-18 18:55	2010-08-19 04:55	2010-08-18 12:55	20.6	69.1			
68	2010-08-08 19:10	2010-08-19 05:10	2010-08-18 12:30	20.5	68.9			
69	2010-08-08 19:25	2010-08-29 05:25	2010-08-18 13:25	20.4	68.7			
70	2010-08-18 19:40	2010-08-19 05:40	2010-08-18 13:40	20.5	68.9			
71	2010-08-08 19:55	2010-08-29-05:55	2010-08-18 13:55	21.5	20.7			
72	2010-08-18 20110	2010-08-19 06:10	2010-08-18 14:00	22.6	72.7			
73	2010-08-18 20:25	2010-08-19 06:25	2010-08-18 14:25	23.1	73.6			
24	2010-08-18 20:40	2010-08-19 06:40	2010-08-18 14:40	23.5	74.3			





PC software is user-friendly for customization, functionality, and reporting. View time and temperature data as a graph or in a spreadsheet. Temperature monitor connects to your computer with a USB cable.

Get the free software download at www.3M.com/temperaturelogger.

Warranty, Limited Remedy, and Disclaimer: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. User is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application. Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.