## all in one, bar graph LED + LCD MOISTURE METER

Model : MS-7003

ISO-9001, CE, IEC1010







The Art of Measurement

## Concrete/Wood, Red LED bar graph + LCD display **MOISTURE METER** Model : MS-7003

## FEATURES

* Designed to c	Designed to check the moisture level of wood, concrete,		
and other non-wood material.			
* 6 % to 40 %	moisture range on wood.		
* 0 to 100% relative moisture value for Concrete and			
other non-wo	od material.		
* Red LED bar	graph indicator and LCD digital display.	R	
* All in one, me	eter build in the test pins.	А	
* Optional sepa	rate probe, available for remote		
measurement			
* Microprocessor circuit assures maximum possible			
accuracy, pro	vides special functions and features.	Р	
* Records Maxi	mum & Minimum reading with recall.	D	
* Data hold function to freeze the desired value on display.			
* Heavy duty &	compact housing case, designed for easy		
carry out & o	peration.	S	
* Built-in low b	attery indicator.	С	
* With auto pov	wer shut off function to prolong the battery	Т	
battery life.		P	
SPECIFICATIO	PNS		
Applications	Designed to check the moisture level of	Р	
	wood, concrete and other non-wood	V	
	material.	C	
Principal	Used the 2 pins electrode to measure the		
	conductive ability of the species, then	А	

Matorial/	Material 1
Material/	Material 1 :
Range	0 to 100% relative moisture value for
	Concrete. and other non-wood material.
	Material 2 :
	6 % to 40 % moisture range on wood.
Resolution	0.1 %.
Accuracy	± ( 5 % + 5 d )
	@ 23± 5 ℃
	@ Material 1 : 13 % to 100%
	@ Material 2 : 6 % to 40%
Probe	2 pins moisture electrode.
Data Hold	By push button on front panel.
Memory Recall	Records Maximum & Minimum reading
	value.
Sampling Time	Approx. 0.8 second.
Operating	0 to 50 $^\circ \mathrm{C}$ ( 32 to 122 $^\circ \mathrm{F}$ ).
Temp./Humidity	Less than 80 %RH.
Power Supply	Alkaline 006P, MN1604 ( PP3 ) DC 9V
	battery.
Power Current	Approx. DC 16 mA.
Weight	251 g/0.55 LB.
Dimension	216.5 x 68.5 x 29.7 mm
	( 8.4 x 2.7 x 1.2 inch ).
Accessories	Instruction manual1 PC.
Included	Extra contact pins1 Set.
Optional	Separate Probe, MP-31
Accessories	Hard Carrying Case, CA-06
	Soft Carrying Case, CA-05A

\* Appearance and specifications listed in this brochure are subject to change without notice.

converter to the reading of % " Moisture

Custom one-chip of microprocessor LSI

LCD size : 51 mm x 37 mm

Digit size : 16 mm ( 0.62 " )

of Content ".

circuit.

Circuit

Display